



FIXED ROOF BRACKETS

19" FOR CONTRACTORS & 16" FOR HOME OWNERS

- For use with various pitches and plank sizes
- 4 offset nail slots (OSHA requires 3) that will not allow the bracket to slide up
- Back-stiffening rib to eliminate twists & flexing
- Smooth edges & rounded corners that will not cut hands or work area
- Easy to set up, operate, reposition, & remove without causing shingle damage
- Dimensions: 19" x 6" x 2" or 16" x 6" x 2"
- Approx weight: 1.5 lbs
- Shipped 12 per box
- Powder coated safety yellow
- Made in America



19" Contractor Bracket

OUR BEST SELLER!

#1

Full 19" Back Keeps Plank Out of Work

#2

Four Nail Slots for Safety

#3

Rib Stiffens to Prevent Twisting

#4

Welded Support Gusset Holds Shape

#5

Squared Heel for Hammer

16" Regular Roof Brackets			
Model #	Length	°	Plank Size
16456	16"	45°	2x6"
16606	16"	60°	2x6"
16904	16"	90°	2x4"
16906	16"	90°	2x6"
19" Contractor Roof Brackets			
Model #	Length	°	Plank Size
19904	19"	90°	2x4"
19606	19"	60°	2x6"
19608	19"	60°	2x8"
19601	19"	60°	2x10"
19456	19"	45°	2x6"
19458	19"	45°	2x8"
19901	19"	90°	2x10"
19906	19"	90°	2x6"
19908	19"	90°	2x8"